

10T hydraulic tensioner

Two-track system

Inno's robust 10T hydraulic tensioner is a simple to operate, reliable system which can be rapidly mobilised for operations around the world.

Sectors

- Renewables
- Communications
- Offshore energy.

Applications

To maintain tension during:

- Pipe and cable handling
- Spooling operations.

Features

- Two vertically mounted track carriages with polyurethane 'V' shaped pads
- One track is fixed to the sub frame while the other track slides on two steel shafts moved by grip cylinders and pivots to accommodate small product diameter variations
- Mounted to base frame via four load cells

- Hydraulic Power Unit (HPU) supplied with a closed loop main pump system for the drive and an auxiliary open loop system for the grip function. Auxiliary boost pump fitted for extra cooling capacity for use with a tensioner capable of low-tension render mode operation.

Benefits

- Tracks are orientated in a vertical plane to allow product to be placed in from the side or pulled through with a leader line
- Reduced deck space
- Easily transportable
- Can take greater vertical loads from product sag / bend
- Can be used in conjunction with Inno's powered hang-off quadrant frame.



INN-10HT-ST 10T hydraulic tensioner

Specifications

Tensioner INN-10HT-ST		HPU	
Dimensions (approx.)	4178 x 1600 x 2549mm	Dimensions (approx.)	2220 x 1310 x 2225mm
Weight (approx.)	6.8T	Weight (approx.)	2.5T
Maximum continuous line pull	10T	Prime mover	75kW; 3 phase; 415/440V; 50/60Hz
Number of tracks	2	Full load current	129 Amps
Track contact length	1.8m	Main pump theoretical displacement	100cc/rev
Max total grip force	40T (20T per track)	Max flow at	1450rpm (50Hz) at 210bar from main transmission pump 142 l/min 1760rpm (60Hz) at 210bar from main transmission pump 170 l/min 1450rpm (50Hz) at 210bar from grip pump 15.95 l/min 1450rpm (60Hz) at 210bar from grip pump 19.14 l/min
Maximum designed speed	1450m/hour	Max operating pressure	250bar
Height - floor to centre of tracks	1327mm		
Track opening	400mm		
Product size range	40-390mm diameter		
Maximum operating pressure	250bar		

Powered hang-off quadrant frame



The 10T hydraulic tensioner can be mounted onto Innovo's powered quadrant frame.

Suspended by a suitable crane, this simple combination is used for product to be pulled out of or laid into baskets prior to lifting onto the vessel.

This arrangement is supplied with a remote control unit, HPU, hoses to reach the quadrant and tensioner whilst suspended and an optional control cabin with Heating, Ventilation, and Air Conditioning (HVAC).

For more information please visit innovoteam.com or email info@innovoteam.com



Innovo is an engineering, construction and equipment rental company. We support the renewables, communications, offshore energy, and marine industries operating worldwide with custom-designed and rental products including jack-up systems, modular pontoons, cable laying equipment, engineering solutions for subsea and offshore applications, and equipment and services for decommissioning.



INNOVO®